

Low Pass Filter

WGLL-14000-1608

50Ω DC to 14000 MHz

Ver. A
2026.05.10


Maximum Rating

Operating Temperature	-55°C~+125°C
Storage Temperature	-55°C~+125°C
RF Input Power	2.5W max at 25°C

Pin Connections

RF Input	1
RF Output	3
Ground	2,4


Outline Drawing



外形尺寸(mm)

A	B	C	D	E	F	G
1.6±0.15	0.8±0.15	0.60±0.15	0.45	0.70	0.15	0.30

推荐PCB布局



单位: inch

Features


- High Performance
- Small Size
- Wide Band
- Ultra Low I.L.
- Temperature Stable
- LTCC Structure

Application

- Harmonic Rejection
- Transmitters/Receivers
- Lab Use



RoHS Compliant





Electrical Specifications⁽¹⁾ at 25°C

Parameter		Frequency (MHz)	MIN	Typ.	MAX	Unit
Pass Band	Insertion Loss	DC-14000	--	1.1	2.1	dB
	Freq. Cut-off	16000	--	3.0	--	dB
	Return Loss	DC-14000	--	12	--	dB
Stop Band	Rejection Loss	19250-22000	20	32	--	dB
		22000-25000	23	31	--	
		25000-26500	20	30	--	

(1) Test on our Demo Board.

(2) This series of products cannot be directly used in DC circuits, If it needs to be used in DC circuits, appropriate capacitors need to be added at the input and output terminals.



Notes:

- The specifications are tested at 25°C±5°C, relative humidity 55~75%.
- Other quality and characteristic not specify in this datasheet. Please contact us for detail requirements.



Well Genius Technology (Shanghai) LTD.

Room 1001, Block C, Hi-Tech Building, No.900 Yi Shan Rd, Shanghai, P.R.C, 200233

Tel: (021) 6495 8888

Fax: (021) 5423 5889

www.wellgenius.com