

Low Pass Filter

WGLL-01800-2012

50Ω

DC to 1800 MHz

Ver. A

2026.07.16

Maximum Rating

Operating Temperature -55°C~+125°C

Storage Temperature -55°C~+125°C

RF Input Power 5.5W max at 25°C


Pin Connections

RF Input 8

RF Output 4

Ground 1,2,3,5,6,7

Outline Drawing




Outline Dimensions (inch)

A	B	C	D	E	F	G	Wt.
.079	.049	.037	.014	.012	.012	.026	grams
2.00	1.25	0.95	0.35	0.30	0.30	0.65	.008

Note: Please refer to case style drawing for details

Demo Board MCL P/N: CG-2012 Suggested PCB Layout




Features


- High Performance
- Small Size
- Wide Band
- Ultra Low I.L.
- Temperature Stable
- LTCC Structure

Application

- Harmonic Rejection
- Transmitters/Receivers
- Lab Use



RoHS Compliant




Functional Schematic

Electrical Specifications⁽¹⁾ at 25°C

Parameter		Frequency (MHz)	MIN	Typ.	MAX	Unit
Pass Band	Insertion Loss	DC-1800	--	1.1	2.2	dB
	Return Loss	DC-1800	--	15	--	dB
	Freq. Cut-Off	1930	--	3.0	--	dB
Stop Band	Rejection Loss	2450-2900	20	35	--	dB
		2900-7000	35	40	--	
		7000-1000	--	35	--	

(1) Test on our Demo Board.



Notes

- The specifications are tested at 25°C±5°C, relative humidity 55~75%.
 - Other quality and characteristic not specify in this datasheet.
- Please contact us for detail requirements.



Well Genius Technology (Shanghai) LTD.

Room 1001, Block C, Hi-Tech Building, No.900 Yi Shan Rd, Shanghai, P.R.C, 200233

Tel: (021) 6495 8888

Fax: (021) 5423 5889

www.wellgenius.com